

# W-Sub

Cinema  
subwoofer



It's impossible to imagine a modern cinema without thunderous deep sound. For the cinemas that long for it, MAG Cinema provides a range of high performance, rigid and reliable cinema subwoofers.


Based on extensive experience of pro-audio, we have built subwoofers designed to withstand most demanding cinema soundtracks imaginable. Own design and production of low-frequency transducers and effective enclosures fit perfectly global cinema experience, which MAG Cinema speakers surely have contributed to.

Featuring large-scale subwoofers for big theaters, main subwoofer channel, smaller solution for more compact cinemas, and specific wall mountable subwoofers for modern 3D sound cinema standards – all of this is provided with MAG Cinema 7-year warranty.

W-Sub is specifically designed for cinemas with extremely tight behind screen space. It is based on high-power, long-excursion 18-inch drivers, and is ready to provide considerable sound pressure and low frequency performance for big-sized theaters.



## DIMENSIONS



## SPECIFICATIONS

Frequency response ( $\pm 3$ dB)	29 – 140 Hz
Sensitivity (1W/1m) (half-space) <sup>1</sup>	100 dB
Max continous SPL <sup>2</sup>	134 dB
LF Transducer	2 x 18"
Impedance	4 Ohm + 4 Ohm (W-Sub-44) 8 Ohm + 8 Ohm (W-Sub-88)
Rated power <sup>3</sup>	LF1 - 1200 W LF2 - 1200 W
Connectors	Phoenix
Dimensions (W x H x D)	1280 x 1110 x 400 mm / 50,39" x 43,70" x 15,75"
Net weight	96,4 kg / 212,53 lbs
Shipping weight	99,4 kg / 219,14 lbs
Enclosure materials	Plywood; wear-resistant paint
Colour	Black

<sup>1</sup>- dB SPL, IEC 60268-5 pink noise, 1W / 1m  
<sup>2</sup>- dB SPL RMS, IEC 60268-5 pink noise, measured on nominal power  
<sup>3</sup>- 2 hour power test, IEC filtered noise, 6 dB crest factor

## SAFETY INSTRUCTIONS

1. Do not pour liquids on speaker system - this may cause driver cone destruction and unappealing speaker appearance. Do not allow direct sunlight on speaker cone - this will reduce its resource dramatically. For fire safety do not install speaker system near open flames or heating elements.
2. Do not use speaker system with damaged speakON or speaker cable - this is an electric shock hazard and fire hazard.
3. Make sure the speaker system is firmly set up on ceiling, stage, or wall (where applicable).
4. While setting speaker system up on slope or slippery surface, make necessary arrangements to avoid its movement due to its vibration.
5. The speaker system is capable of delivering a significant sound pressure levels. To avoid permanent or temporary hearing damage, prolonged exposure to sound pressure levels exceeding 90 dB should be limited.

## CONNECTIONS

Use Hi-pass filter to prevent speaker damage and distorted sound by eliminating low non-audible frequencies in input signal.  
Do not exceed input powers, abovementioned in specifications, while exploiting the speaker system.  
Speaker system comes with barrier strip screw terminal for connection to amplifier.

<b>Connection:</b>	
LF 1 signal +	+ LF1
LF 1 signal -	- LF1
LF 2 signal +	+ LF2
LF 2 signal -	- LF2
<b>High pass filter</b>	29 Hz BW24
Recommended amplifier power	1200 - 2400 W (each driver) on nominal impedance

